

## Hi-Viz General Purpose Wheel Chocks

with SafeRay™ Technology

- Fluoresces under UV light and provides up to 50% more reflectivity compared to the competition.
- Durable and long-lasting properties not only reduce the total cost of ownership but also offer a more sustainable solution.
- Reduces the risk of accidents and boosts operational efficiency.
- All load ratings come from extensively testing pairs of chocks on an 8% grade; please contact the Checkers team for assistance selecting the right chocks for higher or lower grades/loads and specific use cases.


Patent Pending



UC1210-FLG



UC1500-6-FLG




UC1600-FLG

## UC1210

- Recommended tire diameter 95 in to 165 in (241.3 cm to 419.1 cm)
- For mining and construction haul trucks and support equipment
- Max gross vehicle operating weight up to 245,000 lb or 111,130 kg
- For payloads up to 70 tons\* (63,503 kg) use two UC1210
- Recessed carrying handle & mounting hole for ropes, chains or brackets
- Molded-in "How to Use" guidelines

\* Ton is the U.S. standard, equivalent to 2,000 lb (907 kg)




Model	Length	Width	Height	Weight	Color	Prop 65
UC1210-FLG	17 in (43.2 cm)	14 in (35.6 cm)	14 in (35.6 cm)	25 lb (11.3 kg)	SafeRay Green	⚠

Note: Sizing is subject to a manufacturing variance of ±5%

## UC1400

- Recommended tire diameter 27 in to 32 in (68.6 cm to 81.3 cm)
- Standard of the utility industry
- UC1400-4.5 is certified for a gross vehicle operating weight up to 30,000 lb (13,608 kg)
- UC1400-6 is certified for a gross vehicle operating weight up to 60,000 lb (27,216 kg)
- Easy-grip carrying handle & eyebolt for ropes or chains
- Available in singles or pairs (pairs attached with a 48 in long piece of 5/8 in polyester rope)




Model	Length	Width	Height	Weight	Color	Prop 65
UC1400-4.5-FLG	10 in (25.4 cm)	8.5 in (21.6 cm)	5 in (12.7 cm)	4.5 lb (2 kg)	SafeRay Green	⚠
UC1400-4.5-FLG-P				9.5 lb (4.3 kg) (PAIR)		⚠
UC1400-6-FLG				6 lb (2.7 kg)		⚠
UC1400-6-FLG-P				12.5 lb (5.7 kg) (PAIR)		⚠

Note: Sizing is subject to a manufacturing variance of ±5%

## UC1500

- Recommended tire diameter 32 in to 46 in (81.3 cm to 116.8 cm)
- UC1500-4.5 is certified for a gross vehicle operating weight up to 50,000 lb (22,680 kg)
- UC1500-6 is certified for a gross vehicle operating weight up to 70,000 lb (31,751 kg)
- Recessed carrying handle & mounting hole for ropes or chains
- Available in singles or pairs (pairs attached with a 48 in long piece of 5/8 in polyester rope)




Model	Length	Width	Height	Weight	Color	Prop 65
UC1500-4.5 FLG	11.5 in (29.2 cm)	9 in (22.9 cm)	8.5 in (21.6 cm)	4.5 lb (2 kg)	SafeRay Green	⚠
UC1500-4.5-FLG-P				9.5 lb (4.3 kg) (PAIR)		⚠
UC1500-6 FLG				6 lb (2.7 kg)		⚠
UC1500-6-FLG P				12.5 lb (5.7 kg) (PAIR)		⚠

Note: Sizing is subject to a manufacturing variance of ±5%

**⚠ WARNING:** This product can expose you to chemicals including acrylonitrile and styrene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## UC1600

- Recommended tire diameter 27 in to 35 in (68.6 cm to 88.9 cm)
- UC1600 is certified for a gross vehicle operating weight up to 40,000 lb (18,144 kg)
- Recessed carrying handle & mounting hole for ropes or chains
- Available in singles or pairs (pairs attached with a 48 in L piece of 5/8 in polyester rope)




Model	Length	Width	Height	Weight	Color	Prop 65
UC1600-FLG	11.25 in (28.6 cm)	8 in (20.3 cm)	8.25 in (21.0 cm)	3.5 lb (1.6 kg)	SafeRay Green	⚠
UC1600-FLG-P				7.5 lb (3.4 kg) (PAIR)		⚠

Note: Sizing is subject to a manufacturing variance of ±5%

## UC1700

- Recommended tire diameter 27 in to 35 in (68.6 cm to 88.9 cm)
- UC1700 is certified for a gross vehicle operating weight up to 30,000 lb or 13,608 kg
- Recessed carrying handle & mounting hole for ropes or chains
- Available in singles or pairs (pairs attached with a 48 in long piece of 5/8 in polyester rope)




Model	Length	Width	Height	Weight	Color	Prop 65
UC1700-FLG	8.5 in (21.6 cm)	7.5 in (19.1 cm)	6.25 in (15.9 cm)	2.0 lb (.91 kg)	SafeRay Green	⚠
UC1700-FLG-P				4.5 lb (2 kg) (PAIR)		⚠

Note: Sizing is subject to a manufacturing variance of ±5%

## 2000 Series

- Fits the curvature of the tire to absorb wheel-squat during loading and fueling operations
- Features molded-in soft base for increased traction
- 3/8 in x 24 in replaceable polyester rope lanyard connects two chocks together—custom rope lengths available
- Sold in roped pairs



Model	Length	Width	Height	Weight	Color	Prop 65
AC201-FLG	5.5 in (14.0 cm)	4.5 in (11.4 cm)	2.75 in (7.0 cm)	1.5 lb (.68 kg)	SafeRay Green	⚠
UC200-S-FLG				1.6 lb (.7 kg)		⚠


Note: Sizing is subject to a manufacturing variance of ±5%

## UC Series Mounting Brackets for UC1400, UC1500 & UC1700 Series Chocks

UC Series mounting brackets offer a variety of options for safe storage and transportation, decreasing risk and extending the lifespan of your chocks.


### Vertical Brackets

Mounting Hardware NOT included




### Horizontal Brackets

Mounting Hardware NOT included



### Top Brackets

Mounting Hardware NOT included



Model	Description	Coating	Weight
UC14VM	Vertical Mounting Bracket for 1400 Series Wheel Chock. 11.88 in x 10.5 in x 2.13 in	Zinc Plated	2.5 lb (1.1 kg)
UC14HM	Horizontal Underbody Mounting Bracket for 1400 Series Wheel Chock. 11.75 in x 10.25 in x 4.75 in		2.35 lb (1.06 kg)
UC14TM	Horizontal Top Mounting Bracket for 1400 Series Wheel Chock. 10.21 in x 8.92 in x 4.35 in		2.5 lb (1.13 kg)
UC15VM	Vertical Mounting Bracket for 1500 Series Wheel Chock. 11.75 in x 10.25 in x 4.75 in		2.75 lb (1.25 kg)
UC15HM	Horizontal Underbody Mounting Bracket for 1500 Series Wheel Chock. 12 in x 11.5 in x 4.25 in		2.43 lb (1.10 kg)
UC15TM	Horizontal Top Mounting Bracket for 1500 Series Wheel Chock. 11.8 in x 9.17 in x 4.17 in		1.75 lb (0.79 kg)
UC17VM	Vertical Mounting Bracket for 1700 Series Wheel Chock. 10.5 in x 9.25 in x 1.5 in		1.61 lb (0.73 kg)
UC17HM	Horizontal Top Mounting Bracket for 1700 Series Wheel Chock. 8.8 in x 7.785 in x 3.544 in		
MC1900	Universal Dual Mounting Bracket holds 2 each of UC1210 series, or MC3000/4000 series wheel chocks. 36" Length Bracket Rod with 6" x 6" Mounting Plate	Powder Coated Grey	16 lbs (7.3kg)